

# Advantage Color Concentrate

## Description

Advantage Color Concentrate is a heavy bodied, multi-purpose acrylic latex coating fortified with mineral fillers, fibers and high quality pigments for a long-lasting, attractive recreational surface. Advantage Color Concentrate can be used for a top coat, as well as a texture coat containing sand. It is supplied in concentrated form and must be diluted with water prior to application. Advantage Color Concentrate comes in these vibrant colors: light green, dark green, red, tan, blue, maroon, gray and turquoise. Special colors available upon request.

## Uses

Advantage Color Concentrate is used as a colored surface on asphalt and concrete pavements for new and existing tennis courts, playgrounds and recreational surfaces. On-the-job mixing allows improved filling characteristics, simply by adding sand to the mixture.

## Surface Preparation

New asphalt pavements should cure a minimum of 14-21 days prior to any coating application. New concrete surfaces should cure 28 days prior to any coating application. **(When installing over concrete surfaces, the concrete must be installed with a suitable vapor barrier and without concrete curing compounds.)** New and old surfaces should be thoroughly cleaned with compressed air and free from oil, grease, dirt and other foreign matter. Embedded dirt should be brushed thoroughly prior to any coating application. Grease and oil spots should be primed with an approved oil spot primer. See Advantage Specifications for complete information.

## Mix Design-Texture Coat

Most color applications consist of two texture coats. The following mix is recommended for average pavement conditions.

Advantage Color	5 gal.	30 gal.	55 gal.
Silica Sand (Approx 60 mesh to 90 mesh)	30-40 lbs.	180-240 lbs.	330-440 lbs.
Water	2.5-3.0 gal.	15-17 gal.	27-30 gal.

When ordering Advantage Color Concentrate, figure 20-22 yards per gallon of concentrated material for each coat of textured color.

## Mix Design-Top Coat

If a sand-free top coat is desired, Advantage Color Concentrate should be mixed 2 parts concentrated material to 1 part of water. When ordering

Advantage Color Concentrate, figure 24-26 square yards per gallon of concentrated material for each top coat.

## Application

Advantage Color Concentrate is applied with a 50 durometer rubber squeegee. Be sure to squeegee or scrape any excess material left on the surface in order to not leave any ridges. When the first application has dried, the second application shall be made at 90 degrees to the first application.

## Clean-up

Rinse tools with water soon after using. Dried material can be removed with an approved solvent.

## Shelf Life

Approximately 12 months

## Physical Properties

Weight/Gallon ... 9.45 lbs. per gallon

Drying Time ... Touch: 1 hour

Firm: 24 hours

Application Temperature ... 50° F and rising

## Precautions

Keep from freezing. Harmful if swallowed. Read material safety data sheets.

## Shipping Weight

55 gallon drum ... 556 lbs.

30 gallon drum ... 296 lbs.

5 gallon pail ... 48 lbs.

**Warranty:** This product is guaranteed with respect to uniformity and quality. Since its use is beyond the control of the manufacturer, liability for damage shall in no case exceed the purchase price on the quantity of material used. Warranty is void on multi-coat applications if material made by other manufacturers is used with this product.

phone: 800.821.8549

816.923.4325

fax: 816.923.6472

web: [chooseadvantage.com](http://chooseadvantage.com)

► 5201 Brighton

Kansas City, Missouri 64130

Manufactured by Vance Bros Inc