

# Advantage Asphalt Fill

## Description

Advantage Asphalt Fill is a heavy bodied asphalt binder fortified with mineral fillers and fibers. Advantage Asphalt Fill is designed for field mixing with sand to provide superior filling and leveling characteristics. It is supplied in concentrated form and must be diluted with water prior to the application. The amount of sand may be adjusted for varying applications.

## Uses

Advantage Asphalt Fill is recommended for use as a leveling and filler coat for asphalt pavement surfaces on new or existing tennis courts, playgrounds and recreational surfaces. Advantage Asphalt Fill is not recommended for use on concrete surfaces.

## Surface Preparation

New asphalt pavements should cure a minimum of 14-21 days prior to any coating application. New and old surfaces should be thoroughly cleaned with compressed air and free from oil, grease, dirt and other foreign matter. Embedded dirt should be brushed thoroughly prior to any coating application. Grease and oil spots should be primed with an approved oil spot primer. See Advantage Specifications for complete information.

## Mix Design

The following mix is recommended for average pavement conditions. If greater filling is required, an additional coat may be necessary.

Advantage Color	5 gal.	30 gal.	55 gal.
Silica Sand (Approx 40 mesh to 70 mesh)	30-40 lbs.	180-240 lbs.	330-440 lbs.
Water	1.5-2.0 gal.	10-12 gal.	18-20 gal.

When ordering Advantage Asphalt Fill, figure 14-16 square yards per gallon of concentrated material for each coat of textured asphalt fill.

## Application

Advantage Asphalt Fill is applied with a 50 durometer rubber squeegee. Be sure to squeegee or scrape any excess material left on the surface in order to not leave any ridges. When the first application has dried, the second application shall be made at 90 degrees to the first application.

## Clean-up

Rinse tools with water soon after using. Dried material can be removed with an approved solvent.

## Shelf Life

Approximately 12 months

## Physical Properties

Weight/Gallon ... 9.7 lbs. per gallon

Drying Time ... Touch: 1 hour

Firm: 3 hours

Application Temperature ... 50° F and rising

## Precautions

Keep from freezing. Harmful if swallowed. Read material safety data sheets. Do not install Advantage Asphalt Fill on concrete surfaces. Use Advantage Acrylic Fill on concrete surfaces.

## Shipping Weight

55 gallon drum ... 542 lbs.

30 gallon drum ... 277 lbs.

5 gallon pail ... 44 lbs.

**Warranty:** This product is guaranteed with respect to uniformity and quality. Since its use is beyond the control of the manufacturer, liability for damage shall in no case exceed the purchase price on the quantity of material used. Warranty is void on multi-coat applications if material made by other manufacturers is used with this product.

phone: 800.821.8549

816.923.4325

fax: 816.923.6472

web: [chooseadvantage.com](http://chooseadvantage.com)

► 5201 Brighton

Kansas City, Missouri 64130

Manufactured by Vance Bros Inc