

Advantage Sand Filled Color

Description

Advantage Sand Filled Color is a heavy bodied, multipurpose acrylic latex coating fortified for a long-lasting, attractive recreational surface. It is supplied in concentrated form and must be diluted with water prior to application. Advantage Sand Filled Color comes in these vibrant colors: light green, dark green, red, tan, blue, maroon, gray and turquoise. Special colors available upon request

Uses

Advantage Sand Filled Color is used as a colored textured surface on asphalt and concrete pavements for new and existing tennis courts, playgrounds and recreational surfaces.

Surface Preparation

New asphalt pavements should cure a minimum of 14-21 days prior to any coating application. New concrete surfaces should cure 28 days prior to any coating application. **(When installing over concrete surfaces, the concrete must be installed with a suitable vapor barrier and without concrete curing compounds.)** New and old surfaces should be thoroughly cleaned with compressed air and free from oil, grease, dirt and other foreign matter. Embedded dirt should be brushed thoroughly prior to any coating application. Grease and oil spots should be primed with an approved oil spot primer. See Advantage Specifications for complete information.

Mix Design

Most color applications consist of two texture coats. The following mix is recommended for average pavement conditions.

Advantage Color	5 gal.	30 gal.	55 gal.
Water	1.5-2 gal.	11-13 gal.	20-22 gal.

When ordering Advantage Color, figure 16-18 yards per gallon of concentrated material for each coat of textured color.

Application

Advantage Sand Filled Color is applied with a 50 durometer rubber squeegee. Be sure to squeegee or scrape any excess material left on the surface in

order to not leave any ridges. When the first application has dried, the second application shall be made at 90 degrees to the first application.

Clean-up

Rinse tools with water soon after using. Dried material can be removed with an approved solvent.

Shelf Life

Approximately 12 months

Physical Properties

Weight/Gallon ... 13.0 lbs. per gallon

Drying Time ... Touch: 1 hour

Firm: 24 hours

Application Temperature ... 50° F and rising

Precautions

Keep from freezing. Harmful if swallowed. Read material safety data sheets.

Shipping Weight

55 gallon drum ... 724 lbs.

30 gallon drum ... 402 lbs.

5 gallon pail ... 66 lbs.

Warranty: This product is guaranteed with respect to uniformity and quality. Since its use is beyond the control of the manufacturer, liability for damage shall in no case exceed the purchase price on the quantity of material used. Warranty is void on multi-coat applications if material made by other manufacturers is used with this product.

phone: 800.821.8549

816.923.4325

fax: 816.923.6472

web: chooseadvantage.com

► 5201 Brighton

Kansas City, Missouri 64130

Manufactured by Vance Bros Inc